LITEDIMMER*+PLUS AC400 DUO



I ITECEAD

LiteDimmer+ Plus AC400™ is one of our flagship Plus Series power units. Compatible with all LiteMat+ Plus™, LiteTile+ Plus™, and all Plus compatible lighting products, the new Plus Dimmer features a large OLED display that provides visual feedback, and integrated wireless radio that acts as both a transmitter and a receiver for the ultimate wireless convenience. The dimmer also comes with advanced features such as load smoothing, local cueing controls, double circuit control, and a special Master/Slave function that utilizes the integrated wireless card. The unit includes ¼-20 threaded inserts that make rigging or mounting a simple task. The unit also feature K-mount fittings used for attaching battery adapters, mounts, and power supplies.

SPECIFICATIONS (IMPERIAL/METRIC)

POWER RATING:	400W Nominal		
VOLTAGE INPUT:	90~240VAC (264VAC Max.) (Powerco	n)	
VOLTAGE OUTPUT:	Constant Voltage, PWM (PL7 Connector)		
DIMMING RANGE:	0% to 100% Continuous, Flicker-Free		
CONTROLS:	On-Board "ON-OFF" Switch Manual Kelvin Dial Manual Dimming Dial		
SOFTWARE INTERFACE:	Proprietary Connector, Service Center	Upgradeable	
MOUNTING:	(4) 1/4-20 Threaded Inserts Drywall Screw Holes Velcro®/Cable Tie Slots		
AMBIENT TEMP. OPERATION:	-10° to +50° C (14° to 122° F)		
IP RATING:	IP20		

Height Width		Length		Weight			
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lb)	(kg)
2.0	70.4	6.1	15/10	15.0	101.1	4.0	2.2

DIMMER MODEL

LiteDimmer+ Plus AC400 Duo (LD-PLUS-DUO-AC400)

Mounting


ST45 Adapter Plate, Male (LDA-PLUS-KM-M-ST45) ST45 Adapter Plate, Female (LDA-PLUS-KM-F-ST45) LiteMount (w/Convi) (LMA-LITEMOUNT-CONVI) Convi Clamp, Black (LDA-PLUS-CLAMP)

Cable

PL7 Extension, 12 Feet (CA-PL7-EXT-12) PL7 Extension, 24 Feet (CA-PL7-EXT-24)

PL7 TwoFer (CA-PL7.M-PL7.F.2)

PL7 Breakout TwoFer (CA-PL7.M-PL7.F.2-BREAKOUT)





Hours: Monday-Friday 8AM-4:30PM (PST)
Tel: +1 818 358-8542 SMS: +1 818 495-0600
Email: info@litegear.com or support@litegear.com

Web: www.litegear.com



