


Simple and solder-free connections make LiteRibbon more convenient than ever before.

### QuickLinX 90° Angle




**Length:**  
**Width:**  
**Height:**

**3-Conductor**  
1.27 in.  
1.27 in.  
0.19 in.

**5-Conductor**  
1.34 in.  
1.34 in.  
0.19 in.

**6-Conductor**  
1.34 in.  
1.34 in.  
.20 in.

### QuickLinX Tee




**Length:**  
**Width:**  
**Height:**

**3-Conductor**  
1.27 in.  
1.93 in.  
0.19 in.

**5-Conductor**  
1.34 in.  
2.01 in.  
0.19 in.

**6-Conductor**  
2.01 in.  
1.32 in.  
.20 in.

### QuickLinX Cross





**Length:**  
**Width:**  
**Height:**

**3-Conductor**  
1.93 in.  
1.93 in.  
0.19 in.

**5-Conductor**  
2.01 in.  
2.01 in.  
0.19 in.

**6-Conductor**  
2.01 in.  
2.01 in.  
.20 in.

### QuickLinX Coupler





**Length:**  
**Width:**  
**Height:**

**3-Conductor**  
0.64 in.  
0.58 in.  
0.19 in.

**5-Conductor**  
0.64 in.  
0.65 in.  
0.19 in.

**6-Conductor**  
.65 in.  
.65 in.  
.20 in.

### QuickLinX Pro Coupler





**Length:**  
**Width:**  
**Height:**

**3-Conductor**  
0.77 in.  
0.57 in.  
0.27 in.

**5-Conductor**  
0.77 in.  
0.66 in.  
0.28 in.

**6-Conductor**  
0.77 in.  
0.66 in.  
0.28 in.

### QuickLinX Pro to Cable Receiver



**Length:**  
**Width:**  
**Height:**


**3-Conductor**  
0.95 in.  
0.57 in.  
0.27 in.

**5-Conductor**  
0.95 in.  
0.67 in.  
0.28 in.

**6-Conductor**  
0.95 in.  
0.67 in.  
0.28 in.

Simple and solder-free connections make LiteRibbon more convenient than ever before.

### QuickLinx to QuickLinx Cable



**Length:**  
**Width:**  
**Height:**

#### 3-Conductor

7 in.  
0.58 in.  
0.19 in.


#### 5-Conductor

7 in.  
0.65 in.  
0.19 in.

#### 6-Conductor

7 in.  
0.65 in.  
.20 in.

### QuickLinx to Bare-Ends



**Length:**  
**Width:**  
**Height:**

#### 3-Conductor

6.5 in.  
0.58 in.  
0.19 in.

#### 5-Conductor

6.5 in.  
0.65 in.  
0.19 in.

#### 6-Conductor

6.5 in.  
0.65 in.  
.20 in.